

Comply and compatible with 19 inch international standard, metric system and ETSI standard. Frame is built up by double pipes profile and appropriate 3 tees joint for solid structure and static loading achieves to 1500 kg.


High density vented hole front and rear door, meeting the ventilation requirements.



Front View


Product Description

Product Type	Heavy Duty Close Rack
Product ID	PRO9032
Size	32U
Weight	± 139 kg
Dimension (DxWxH)	900 x 600 x 1620 mm
Complete Set with	<ul style="list-style-type: none"> • Perforated Front Door, Steel Rear Door and 2 Side Door with lock • 1 Unit Horizontal PDU 8 outlet with switch • 1 Unit Bracket Modular with 2 Fan • 1 pc Fixed Shelf • 1 pc Bottom Cover • 4 pcs Mounting Profile • 4 pcs Adjustable Foot • 4 pcs Castors • 50 set Cagenuts & Screws

Product Drawing


1. Main Frame
2. Front Door
3. Front Door Lock
4. Left Rear Door
5. Right Rear Door
6. Rear Door Lock
7. Side Doors
8. Top Panel
9. Castor Tray
10. Castor
11. Adjustable Feet
12. Mounting Angle
13. 19inch Mounting Profile



Back View



The side door easy to be installed & uninstalled quickly which make the working conveniently. Include castor & adjustable feet which make the moving and fixing easily.

Front and rear door angle can open 130 degree with top cable entry hole with rubber cover. Comfortable handle with safe lock & rear door 3-point handle lock system enlarges the security.



Product Drawing

