Comply and compatible with 19 inch international standard, metric system and FTSI standard, Frame is built up by double pipes profile and appropriative 3 tees joint for solid structure and static loading achieves to 1500 kg

High density vented hole front and rear door, meeting the ventilation requirements.

Product Description	
Product Type	Heavy Duty Close Rack
Product ID	PRO9020
Size	20U
Weight	± 115 kg
Dimension (DxWxH)	900 x 600 x 1100 mm
Complete Set with	Perforated Front Door, Steel Rear Door and 2 Side Door with lock Unit Horizontal PDU 8 outlet with switch Unit Bracket Modular with 2 Fan Torized Shelf

· 1 pc Bottom Cover 4 pcs Mounting Profile 4 pcs Adjustable Foot 4 pcs Castors . 50 set Cagenuts & Screws







## Product Drawing



- Main Frame
- Front Door
- Front Door Lock
- Left Rear Door
- Right Rear Door
- Rear Door Lock
- Side Doors
- Top Panel
- Castor Tray
- 10. Castor
- 11 Adjustable Feet
- 12. Mounting Angle
- 13. 19inch Mounting Profile



The side door easy to be installed & uninstalled quickly which make the working conveniently. Include castor & adjustable feet which make the moving and fixing easily.

Front and rear door angle can open 130 degree with top cable entry hole with rubber cover. Comfortable handle with safe lock & rear door 3-point handle lock system enlarges the security.



## Product Drawing

